



US005592811A

United States Patent [19]

Dodge et al.

[11] Patent Number: 5,592,811

[45] Date of Patent: Jan. 14, 1997

[54] METHOD AND APPARATUS FOR THE
DESTRUCTION OF VOLATILE ORGANIC
COMPOUNDS

[75] Inventors: Paul R. Dodge, Mesa; Robert S.
McCarty, Phoenix, both of Ariz.; Doug
Rogers, Visalia; Gail Rogers, San
Gabriel, both of Calif.

[73] Assignee: AlliedSignal Inc., Morris Township,
N.J.

[21] Appl. No.: 538,692

[22] Filed: Oct. 3, 1995

[51] Int. Cl.⁶ F02C 6/18; F02G 3/00

[52] U.S. Cl. 60/39.02; 60/39.07; 60/39.27;
60/731; 60/733; 60/746; 60/760; 422/182;
431/5

[58] Field of Search 60/731, 733, 746,
60/39.23, 39.27, 39.02, 39.12, 760; 422/182,
183; 431/5, 353, 352

[56] References Cited

U.S. PATENT DOCUMENTS

2,718,753 9/1955 Bridgeman .
2,718,755 9/1955 Heller .
3,380,250 4/1968 Whatley .
3,846,979 11/1974 Pfeifferle 60/733
4,226,083 10/1980 Lewis et al. .
4,236,464 12/1980 Anderson et al. 431/5
4,292,801 10/1981 Wilkes et al. .
4,299,086 11/1981 Madgavkar et al. .
4,339,924 7/1982 White et al. .

4,374,184 2/1993 Somers et al. .
4,420,929 12/1983 Jorgensen et al. .
4,458,481 7/1984 Ernst 60/760
4,550,563 11/1985 Marchand .
4,702,073 10/1987 Melconian .
4,820,594 4/1989 Sugita et al. .
4,864,811 9/1989 Pfeifferle .
4,910,957 3/1990 Moreno et al. .
4,974,530 12/1990 Lyon 431/5
5,070,700 12/1991 Mowill 60/746
5,108,717 4/1992 Deller et al. 422/182
5,237,812 8/1993 Mumford .
5,307,621 5/1994 Glassman et al. .
5,369,947 12/1994 Dummersdorf et al. .
5,417,052 5/1995 Bharathan et al. 60/39.02

Primary Examiner—Charles G. Freay

Attorney, Agent, or Firm—James W. McFarland

[57] ABSTRACT

A system for the destruction of volatile organic compounds while generating power. In a preferred embodiment the system comprises a combustor and a reaction chamber connected to an exit of the combustor. A primary inlet to the combustor supplies a primary fuel to the combustor. A secondary fuel, comprising air and an amount of one or more volatile organic compounds, is supplied to a compressor, which compresses the secondary fuel and directs the secondary fuel to the combustor and the reaction chamber. The system is suitably configured to enable the stoichiometric reaction of the two fuels in a manner sufficient to destroy the volatile organic compounds contained in the secondary fuel and power a turbine engine connected to an exit of the reaction chamber.

17 Claims, 5 Drawing Sheets

